

BORING HEAD WITH SHANKS



Cat No.	Head	Mounting	Overall	Max.	Center	Cross
	Diameter	Thread Size	Length	Off Set	Distance	Vertical
					B/W Holes	Hole Size
GPH-8037	2"	7/8"x20 UNF	2-13/32"	3/4"	5/8"	1/2"
GPH-8038	2"	1-1/2x18 TPI	2-13/32"	3/4"	5/8"	1/2"
GPH-8038M	50mm	1-1/2x18 TPI	60mm	20mm	5/8"	12mm
GPH-8039	3"	1-1/2x18 TPI	3-5/32"	1"	15/16"	3/4"
GPH-8040	4"	1-1/2x18 TPI	3-3/4"	1-5/8"	1-1/4"	1"
SPARE SHANKS						
Cat No.	Shank	Mounting	Cat No.	Mounting	Drawbar	
	Style	Thread		Thread	Thread	
METRIC SHANKS						
GSS-8064	R8	7/8"-20 TPI	GSS-8069	1-1/2"X18 TPI	7/16" UNF	
GSS-8065	MT-2	7/8"-20 TPI	GSS-8070	1-1/2"X18 TPI	M10	
GSS-8066	MT-3	7/8"-20 TPI	GSS-8071	1-1/2"X18 TPI	M12	
GSS-8067	ISO 30	7/8"-20 TPI	GSS-8072	1-1/2"X18 TPI	M12	
GSS-8068	ISO 40	7/8"-20 TPI	GSS-8073	1-1/2"X18 TPI	M16	
IMPERIAL SHANKS						
GSS-8046	R8	7/8"-20 TPI	GSS-8053	1-1/2"X18 TPI	7/16" UNF	
GSS-8047	MT-2	7/8"-20 TPI	GSS-8054	1-1/2"X18 TPI	3/8" BSW	
GSS-8048	MT-3	7/8"-20 TPI	GSS-8055	1-1/2"X18 TPI	1/2" BSW	
GSS-8060	ISO 30	7/8"-20 TPI	GSS-8062	1-1/2"X18 TPI	1/2" BSW	
GSS-8061	ISO 40	7/8"-20 TPI	GSS-8063	1-1/2"X18 TPI	5/8" BSW	

